

# Sleepyheads Flannel



pattern tested

 **Clothworks**<sup>TM</sup>  
Inspired. Inspiring.

Featuring fabrics from the  
**Sleepyheads Flannel** collection  
by Diane Knott  
Finished size: 54" x 54"  
*Design by Susan Allen for Clothworks*

## Materials

Yardages based on 42" wide fabric

- 2/3 Yard or one Panel (Y0146-1)
- 1/2 Yard - Green Tonal (Y0148-4)
- 1/8 Yard - Cream Floral (Y0151-4)
- 1/8 Yard - Pink Floral (Y0151-2)
- 1/8 Yard - Blue Floral (Y0151-3)
- 1/8 Yard - Yellow Mini Floral (Y0152-1)
- 1/8 Yard - Blue Tonal (Y0148-3)
- 1/8 Yard - Pink Tonal (Y0148-2)
- 1/8 Yard - Yellow Tonal (Y0148-1)
- 1/8 Yard - Cream Toy Toss (Y0150-1)
- 1 1/4 Yards - Pictorial Stripe (Y0147-1)
- 1 3/8 Yards - Yellow Animal Toss (Y0149-1)
- OR Blue Animal Toss (Y0149-3)
- OR Pink Animal Toss (Y0149-2) for outer border
- 1/2 Yard - Yellow Tonal (Y0148-1)
- OR Blue Tonal (Y0148-3)
- OR Pink Tonal (Y0148-2) for binding
- 3 1/2 Yards—Backing of choice

## Cut the Fabrics

WOF = Width of Fabric

LOF = Length of Fabric

### From the Panel cut:

- 1 – Trim leaving at least 1/4" seam allowance outside the panel images. See Step 1.

### From the Green Tonal cut:

- 4 – 3" x WOF strips (Trim each strip to 26")

### From EACH 1/8 yard block border fabric (8 fabrics) cut:

- 4 – 4" x 4" squares for a total of 32 squares

### From the Pictorial Stripe fussy cut:

- 4 – 5-1/2" x 45" LOF strips

### From the Animal Toss cut:

- 6 – 7" x WOF strips

### From the 1/2 yard Tonal cut:

- 6 – 2-1/2" x WOF (binding)

## Directions

Prior to starting this project, please check our web site for any updates: [www.clothworkstextiles.com](http://www.clothworkstextiles.com).

### Assembly Instructions:

1. Sew a 3" x 26" Green Tonal strip to the right and left edges of the panel. Trim the excess fabric from the strip where it extends past the top and bottom of the panel and press. Sew a 3" x 26" Green Tonal strip to the top and bottom edges of the panel. Trim the excess fabric from the strip where it extends past the left and right edges and press. Trim this completed panel section and borders to measure 25" x 25".
2. Sew (7) 4" x 4" border squares end-to-end to make a 4" x 25" pieced side border. Repeat for second side border. Sew borders to the right and left sides of the quilt top and press seams away from the center of the quilt. Sew (9) 4" x 4" border squares end-to-end to make a 4" x 32" pieced top border. Repeat for bottom border. Sew borders to the top and bottom of the quilt top and press seams away from the center of the quilt.
3. Center and pin a stripe border strip in place. Sew the seam by starting and ending 1/4" from raw edge, backstitch to secure and press seam toward the quilt top. Repeat on the remaining three edges (Figure 1).
4. Lay quilt top right side up on your ironing board and fold each border end flat back onto itself, right sides together, forming a 45 degree angle at the quilt corner. Press to form a crease (Figure 2).
5. Fold the quilt with right sides together. Line up border stripe raw edges, border seams at the 1/4" backstitched point, and pressed creases and pin in place. Stitch along the crease, backstitching at 1/4" border seam. Repeat on the remaining three corners (Figure 3).
6. Press seam open. With quilt right side up, align 45 degree angle line of a square ruler on seam line to check accuracy. If corner is flat and square, trim excess fabric to 1/4" seam allowance. Repeat for all 4 corners. Quilt top should measure 42" square.
7. Remove selvages from the 7" x WOF outer border strips and sew end-to-end. Subcut, in this order, (2) 7" x 55" borders and (2) 7" x 42" borders. Sew the 42" outer borders to each side of the quilt top and press towards border. Sew the 55" outer borders to the top and bottom of the quilt top and press towards border.
8. Layer the quilt top, batting, and backing and quilt as desired. Add binding to the quilt.




Figure 1




Figure 2




Figure 3

While every attempt has been made to give accurate measurements, yardage requirements, and construction directions, this does not allow for personal variations in measuring, cutting and/or sewing. Clothworks is not responsible for printing errors.